



The long-life shunts are used to extend the current measuring range of moving-coil meters for the reliable display and processing of direct currents, especially at high currents of up to 15000A.
The direct current flowing through the shunt generates a proportional voltage drop, which can be displayed for example with a moving-coil measuring device connected in parallel or processed electronically.
The shunts comply with DIN 43703 and DIN EN 60051.
Class 0.2 on request

Technical data	
Accuracy class	0,5
Input	1, 1.5, 2.5, 4, 6, 10, 15, 25, 40, 60, 100, 150 A
Output	150 mV

Variants (12)

Article no.	Description
70032-1028	Shunt 1A/150mV Kl. 0,5 mit Isoliersockel
70032-1029	Shunt 1,5A/150mV Kl. 0,5 mit Isoliersockel
70032-1030	Shunt 2,5A/150mV Kl. 0,5 mit Isoliersockel
70032-1031	Shunt 4A/150mV Kl. 0,5 mit Isoliersockel
70032-1032	Shunt 6A/150mV Kl. 0,5 mit Isoliersockel
70032-1033	Shunt 10A/150mV Kl. 0,5 mit Isoliersockel
70032-1034	Shunt 15A/150mV Kl. 0,5 mit Isoliersockel
70032-1035	Shunt 25A/150mV Kl. 0,5 mit Isoliersockel
70032-1036	Shunt 40A/150mV Kl. 0,5
70032-1037	Shunt 60A/150mV Kl. 0,5
70032-1038	Shunt 100A/150mV Kl. 0,5
70032-1039	Shunt 150A/150mV Kl. 0,5