



- Article features
- This protective current transformer is used for system protection in conjunction with the appropriate switching devices
 - Available in numerous protection classes
 - Sealable secondary terminal covers made of clear polycarbonate
 - Double secondary terminals on all versions for short-circuiting the secondary windings before opening the secondary circuit

Technical data	
Round conductor	∅ 23 mm
Primary rail	30 x 10 mm
Dimensions (W × H × D)	76 × 105 × 50 mm
Instrument security factor	FS 5

Types (72)

Output	Cl.	Rated current A							
		75	100	125	150	200	250	300	
1 A	5P5	1.25 VA 70097-3982	2.5 VA 70030-2665	2.5 VA 70030-2666	3.75 VA 70097-3932	5 VA 70030-2667	7.5 VA 70030-2668	7.5 VA 70030-2669	
	5P10	–	–	1.25 VA 70030-2649	1.25 VA 70030-2650	1.25 VA 70030-2651	2.5 VA 70030-2652	2.5 VA 70030-2653	
	10P5	1.25 VA 70030-2673	2.5 VA 70030-2674	2.5 VA 70030-2675	3.75 VA 70030-2676	5 VA 70030-2677	7.5 VA 70030-2678	7.5 VA 70030-2679	
	10P10	–	–	1.25 VA 70030-2657	1.25 VA 70030-2658	1.25 VA 70030-2659	2.5 VA 70030-2660	3.75 VA 70030-2661	
5 A	5P5	1.25 VA 70030-2630	2.5 VA 70030-2631	2.5 VA 70097-4021	3.75 VA 70030-2632	5 VA 70030-2633	7.5 VA 70030-2634	7.5 VA 70030-2635	
	5P10	–	–	1.25 VA 70097-4023	1.25 VA 70030-2618	1.25 VA 70097-4025	2.5 VA 70097-4210	2.5 VA 70097-3906	
	10P5	1.25 VA 70030-2639	2.5 VA 70030-2640	2.5 VA 70030-2641	3.75 VA 70030-2642	5 VA 70030-2643	7.5 VA 70030-2644	7.5 VA 70030-2645	
	10P10	–	–	1.25 VA 70030-2622	1.25 VA 70030-2623	1.25 VA 70030-2624	2.5 VA 70030-2625	3.75 VA 70030-2626	

		400	500	600
1 A	5P5	5 VA 70030-2670	5 VA 70030-2671	7 VA 70030-2672
	5P10	1.25 VA 70030-2654	1.25 VA 70030-2655	1.25 VA 70030-2656
	10P5	5 VA 70030-2680	5 VA 70030-2681	5 VA 70030-2682
	10P10	1.25 VA 70030-2662	1.25 VA 70030-2663	1.25 VA 70030-2664
5 A	5P5	5 VA 70030-2636	5 VA 70030-2637	5 VA 70030-2638

		400	500	600
	5P10	1.25 VA 70030-2619	1.25 VA 70030-2620	1.25 VA 70030-2621
	10P5	5 VA 70030-2646	5 VA 70030-2647	5 VA 70030-2648
	10P10	1.25 VA 70030-2627	1.25 VA 70030-2628	1.25 VA 70030-2629

Special designs on request:

- any primary and secondary rated currents
- operating voltage series 1 (1,2kV)
- Cast resin grouting