



Article features

- This protective current transformer is used for system protection in conjunction with the appropriate switching devices
- Available in numerous protection classes
- Sealable secondary terminal covers made of clear polycarbonate
- Double secondary terminals on all versions for short-circuiting the secondary windings before opening the secondary circuit

Technical data	
Round conductor	Ø 44 mm
Primary rail	30 x 15 mm, 60 x 12 mm, 2 x 50 x 10 mm, 4 x 30 x 10 mm
Dimensions (W x H x D)	90 x 115 x 57 mm
Instrument security factor	FS 5

Types (34)

Output	Cl.	Rated current A						
		400	500	600	750	800	1000	1200
1 A	5P5	1.25 VA 70030-2907	2.5 VA 70030-2908	2.5 VA 70030-2909	3.75 VA 70030-2910	3.75 VA 70030-2911	5 VA 70097-4043	3.75 VA 70030-2912
	10P5	1.25 VA 70030-2914	2.5 VA 70030-2915	2.5 VA 70030-2916	3.75 VA 70030-2917	3.75 VA 70030-2918	5 VA 70030-2919	3.75 VA 70030-2920
	10P10	–	–	–	–	–	2.5 VA 70030-2904	–
5 A	5P5	1.25 VA 70030-2937	1.25 VA 70030-4911	2.5 VA 70097-3927	2.5 VA 70030-4912	2.5 VA 70030-4913	2.5 VA 70030-4914	1.25 VA 70030-4915
	10P5	1.25 VA 70030-2943	1.25 VA 70030-4905 2.5 VA 70030-2944	2.5 VA 70030-2945	2.5 VA 70030-4906	2.5 VA 70030-4907	2.5 VA 70030-4908	1.25 VA 70030-4909
1500								
1 A	5P5	5 VA 70030-2913						
	10P5	5 VA 70030-2921						
5 A	5P5	1.25 VA 70030-4916						
	10P5	1.25 VA 70030-4910						

Special designs on request:

- any primary and secondary rated currents
- operating voltage series 1 (1,2kV)
- Cast resin grouting