



- Article features
- This protective current transformer is used for system protection in conjunction with the appropriate switching devices
 - Available in numerous protection classes
 - Sealable secondary terminal covers made of clear polycarbonate
 - Double secondary terminals on all versions for short-circuiting the secondary windings before opening the secondary circuit

Technical data	
Primary rail	30 x 15 mm, 80 x 12 mm, 100 x 10 mm, 3 x 100 x 10 mm
Dimensions (W x H x D)	140 x 182 x 60 mm
Instrument security factor	FS 5

Types (28)

Output	Cl.	Rated current A						
		1000	1200	1500	1600	2000	2500	3000
1 A	5P10	5 VA 70030-4740	5 VA 70030-4903	5 VA 70030-4742	5 VA 70030-4743	7.5 VA 70097-9155	7.5 VA 70030-4745	10 VA 70030-4746
	10P10	5 VA 70030-4747	7.5 VA 70030-4748	5 VA 70030-4749	5 VA 70030-4750	7.5 VA 70030-4751	7.5 VA 70030-4752	10 VA 70030-4753
5 A	5P10	5 VA 70030-4754	5 VA 70030-4904	5 VA 70030-4756	5 VA 70030-4757	7.5 VA 70030-4758	7.5 VA 70030-4759	10 VA 70030-4760
	10P10	5 VA 70030-4761	7.5 VA 70030-4762	5 VA 70030-4763	5 VA 70030-4764	7.5 VA 70030-4765	7.5 VA 70030-4766	10 VA 70030-4767

- Special designs on request:
- any primary and secondary rated currents
 - operating voltage series 1 (1,2kV)
 - Cast resin grouting