



- Article features
- This protective current transformer is used for system protection in conjunction with the appropriate switching devices
  - Available in numerous protection classes
  - Sealable secondary terminal covers made of clear polycarbonate
  - Double secondary terminals on all versions for short-circuiting the secondary windings before opening the secondary circuit

| Technical data             |                                                      |
|----------------------------|------------------------------------------------------|
| Primary rail               | 30 x 15 mm, 80 x 12 mm, 100 x 10 mm, 3 x 100 x 10 mm |
| Dimensions (W x H x D)     | 140 x 182 x 60 mm                                    |
| Instrument security factor | FS 5                                                 |

Types (28)

| Output | Cl.   | Rated current A |                   |                 |                 |                   |                   |                  |
|--------|-------|-----------------|-------------------|-----------------|-----------------|-------------------|-------------------|------------------|
|        |       | 1000            | 1200              | 1500            | 1600            | 2000              | 2500              | 3000             |
| 1 A    | 5P10  | 5 VA 70030-4740 | 5 VA 70030-4903   | 5 VA 70030-4742 | 5 VA 70030-4743 | 7.5 VA 70097-9155 | 7.5 VA 70030-4745 | 10 VA 70030-4746 |
|        | 10P10 | 5 VA 70030-4747 | 7.5 VA 70030-4748 | 5 VA 70030-4749 | 5 VA 70030-4750 | 7.5 VA 70030-4751 | 7.5 VA 70030-4752 | 10 VA 70030-4753 |
| 5 A    | 5P10  | 5 VA 70030-4754 | 5 VA 70030-4904   | 5 VA 70030-4756 | 5 VA 70030-4757 | 7.5 VA 70030-4758 | 7.5 VA 70030-4759 | 10 VA 70030-4760 |
|        | 10P10 | 5 VA 70030-4761 | 7.5 VA 70030-4762 | 5 VA 70030-4763 | 5 VA 70030-4764 | 7.5 VA 70030-4765 | 7.5 VA 70030-4766 | 10 VA 70030-4767 |

- Special designs on request:
- any primary and secondary rated currents
  - operating voltage series 1 (1,2kV)
  - Cast resin grouting