



- Article features
- This protective current transformer is used for system protection in conjunction with the appropriate switching devices
 - Available in numerous protection classes
 - Sealable secondary terminal covers made of clear polycarbonate
 - Double secondary terminals on all versions for short-circuiting the secondary windings before opening the secondary circuit

Technical data	
Round conductor	∅ 80 mm
Dimensions (W × H × D)	133 × 155 × 46 mm
Instrument security factor	FS 5

Types (94)

Output	Cl.	Rated current A						
		250	300	400	500	600	750	800
1 A	5P5	2.5 VA 70030-3703	3.75 VA 70030-3704	5 VA 70030-3705	7.5 VA 70030-3706	5 VA 70030-3707	7.5 VA 70030-3708	7.5 VA 70030-3709
	5P10	–	1.25 VA 70030-3682	1.25 VA 70097-3985	2.5 VA 70030-3683	1.25 VA 70030-3684	2.5 VA 70030-3685	1.25 VA 70030-3686
	10P5	2.5 VA 70030-3715	3.75 VA 70030-3716	5 VA 70030-3717	7.5 VA 70030-3718	5 VA 70030-3719	7.5 VA 70030-3720	7.5 VA 70030-3721
	10P10	1.25 VA 70030-3691	1.25 VA 70030-3692	1.25 VA 70030-3693	2.5 VA 70030-3694	1.25 VA 70030-3695	2.5 VA 70030-3696	1.25 VA 70030-3697
5 A	5P5	2.5 VA 70030-3749	3.75 VA 70030-3750	5 VA 70030-3751	7.5 VA 70030-3752	5 VA 70030-3753	7.5 VA 70030-3754	7.5 VA 70030-3755
	5P10	–	1.25 VA 70030-3727	1.25 VA 70030-3728	2.5 VA 70030-3729	1.25 VA 70097-3426	2.5 VA 70030-3730	1.25 VA 70030-3731
	10P5	2.5 VA 70030-3761	3.75 VA 70030-3762	5 VA 70030-3763	7.5 VA 70097-4061	5 VA 70030-3764	7.5 VA 70097-4062	7.5 VA 70030-3765
	10P10	1.25 VA 70030-3737	1.25 VA 70030-3738	1.25 VA 70030-3739	2.5 VA 70030-3740	1.25 VA 70030-3741	2.5 VA 70030-3742	1.25 VA 70030-3743

		1000	1200	1500	1600	2000
1 A	5P5	10 VA 70030-3710	10 VA 70030-3711	15 VA 70030-3712	15 VA 70030-3713	20 VA 70030-3714
	5P10	2.5 VA 70030-3687	2.5 VA 70030-3688	5 VA 70030-3689	5 VA 70030-3690	5 VA 70097-4218
	10P5	10 VA 70030-3722	10 VA 70030-3723	15 VA 70030-3724	15 VA 70030-3725	20 VA 70030-3726
	10P10	2.5 VA 70030-3698	3.75 VA 70030-3699	5 VA 70030-3700	5 VA 70030-3701	5 VA 70030-3702
5 A	5P5	10 VA 70030-3756	10 VA 70030-3757	15 VA 70030-3758	15 VA 70030-3759	20 VA 70030-3760

		1000	1200	1500	1600	2000
	5P10	2.5 VA 70030-3732	2.5 VA 70030-3733	5 VA 70030-3734	5 VA 70030-3735	5 VA 70030-3736
	10P5	10 VA 70030-3766	10 VA 70030-3767	15 VA 70030-3768	15 VA 70030-3769	20 VA 70030-3770
	10P10	2.5 VA 70030-3744	3.75 VA 70030-3745	5 VA 70030-3746	5 VA 70030-3747	5 VA 70030-3748

Special designs on request:

- any primary and secondary rated currents
- operating voltage series 1 (1,2kV)
- Cast resin grouting