




Article features

- This protective current transformer is used for system protection in conjunction with the appropriate switching devices
- Available in numerous protection classes
- Sealable secondary terminal covers made of clear polycarbonate
- Double secondary terminals on all versions for short-circuiting the secondary windings before opening the secondary circuit

Technical data

Round conductor	∅ 50 mm
Primary rail	30 x 15 mm, 60 x 12 mm, 3 x 60 x 10 mm, 4 x 50 x 10 mm
Dimensions (W x H x D)	133 x 155 x 46 mm
Instrument security factor	FS 5

Types (98)

Output	Cl.	Rated current A						
		250	300	400	500	600	750	800
1 A	5P5	2.5 VA 70030-3790	3.75 VA 70030-3791	5 VA 70030-3792	7.5 VA 70030-3793	5 VA 70030-3794	7.5 VA 70030-3795	7.5 VA 70030-3796
	5P10	–	1.25 VA 70030-3771	1.25 VA 70030-3772	2.5 VA 70030-3773	1.25 VA 70030-3774	2.5 VA 70030-3775	1.25 VA 70030-3776
	10P5	2.5 VA 70030-3802	3.75 VA 70030-3803	5 VA 70030-3804	7.5 VA 70030-3805	5 VA 70030-3806	7.5 VA 70030-3807	7.5 VA 70030-3808
	10P10	1.25 VA 70030-3782	1.25 VA 70097-8015	1.25 VA 70030-3783	2.5 VA 70030-3784	1.25 VA 70097-8019 5 VA 70097-8019-0500	2.5 VA 70030-3785	1.25 VA 70097-8021 5 VA 70097-8021-0500
5 A	5P5	2.5 VA 70030-3837	3.75 VA 70030-3838	5 VA 70030-3839	7.5 VA 70030-3840	5 VA 70030-3841	7.5 VA 70030-3842	7.5 VA 70030-3843
	5P10	–	1.25 VA 70030-3814	1.25 VA 70030-3815	2.5 VA 70030-3816	1.25 VA 70030-3817	2.5 VA 70030-3818	1.25 VA 70030-3819
	10P5	2.5 VA 70030-3849	3.75 VA 70030-3850	5 VA 70030-3851	7.5 VA 70030-3852	5 VA 70030-3853	7.5 VA 70030-3854	7.5 VA 70030-3855
	10P10	1.25 VA 70030-3825	1.25 VA 70030-3826	1.25 VA 70030-3827	2.5 VA 70030-3828	1.25 VA 70030-3829	2.5 VA 70030-3830	1.25 VA 70030-3831

		1000	1200	1500	1600	2000
1 A	5P5	10 VA 70030-3797	10 VA 70030-3798	15 VA 70030-3799	15 VA 70030-3800	20 VA 70030-3801
	5P10	2.5 VA 70030-3777	2.5 VA 70030-3778	5 VA 70030-3779	5 VA 70030-3780	5 VA 70030-3781
	10P5	10 VA 70030-3809	10 VA 70030-3810	15 VA 70030-3811	15 VA 70030-3812	20 VA 70030-3813
	10P10	2.5 VA 70097-8022 5 VA 70097-8022-0500	3.75 VA 70030-3786	5 VA 70030-3787	5 VA 70030-3788	5 VA 70030-3789

		1000	1200	1500	1600	2000
5 A	5P5	10 VA 70030-3844	10 VA 70030-3845	15 VA 70030-3846	15 VA 70030-3847	20 VA 70030-3848
	5P10	2.5 VA 70030-3820	2.5 VA 70030-3821	5 VA 70030-3822	5 VA 70030-3823	5 VA 70030-3824
	10P5	10 VA 70030-3856	10 VA 70030-3857	15 VA 70030-3858	15 VA 70030-3859	20 VA 70030-3860
	10P10	2.5 VA 70030-3832	3.75 VA 70030-3833	5 VA 70030-3834	5 VA 70030-3835	5 VA 70030-3836

Special designs on request:

- any primary and secondary rated currents
- operating voltage series 1 (1,2kV)
- Cast resin grouting