



- Article features
- This protective current transformer is used for system protection in conjunction with the appropriate switching devices
 - Available in numerous protection classes
 - Sealable secondary terminal covers made of clear polycarbonate
 - Double secondary terminals on all versions for short-circuiting the secondary windings before opening the secondary circuit

Technical data	
Round conductor	∅ 30 mm
Primary rail	30 x 15 mm, 80 x 12 mm, 2 x 80 x 10 mm, 4 x 30 x 10 mm
Dimensions (W x H x D)	133 x 155 x 46 mm
Instrument security factor	FS 5

Types (95)

Output	Cl.	Rated current A						
		250	300	400	500	600	750	800
1 A	5P5	2.5 VA 70030-3883	3.75 VA 70030-3884	5 VA 70030-3885	7.5 VA 70030-3886	5 VA 70030-3887	7.5 VA 70030-3888	7.5 VA 70030-3889
	5P10	–	1.25 VA 70030-3861	1.25 VA 70030-3862	2.5 VA 70030-3863	1.25 VA 70030-3864	2.5 VA 70030-3865	1.25 VA 70030-3866
	10P5	2.5 VA 70030-3895	3.75 VA 70030-3896	5 VA 70030-3897	7.5 VA 70030-3898	5 VA 70030-3899	7.5 VA 70030-3900	7.5 VA 70030-3901
	10P10	1.25 VA 70030-3872	1.25 VA 70030-3873	1.25 VA 70030-3874	2.5 VA 70030-3875	1.25 VA 70030-3876	2.5 VA 70030-3877	1.25 VA 70030-3878
5 A	5P5	2.5 VA 70030-3924	3.75 VA 70030-3925	5 VA 70030-3926	7.5 VA 70030-3927	5 VA 70030-3928	7.5 VA 70030-3929	7.5 VA 70030-3930
	5P10	–	1.25 VA 70030-3907	1.25 VA 70030-3908	2.5 VA 70030-3909	1.25 VA 70030-3910	2.5 VA 70030-3911	1.25 VA 70097-3834
	10P5	2.5 VA 70030-3936	3.75 VA 70030-3937	5 VA 70030-3938	7.5 VA 70030-3939	5 VA 70030-3940	7.5 VA 70030-3941	7.5 VA 70030-3942
	10P10	1.25 VA 70030-3913	1.25 VA 70030-3914	1.25 VA 70030-3915	2.5 VA 70030-3916	1.25 VA 70030-3917	2.5 VA 70030-3918	1.25 VA 70030-3919

		1000	1200	1500	1600	2000
1 A	5P5	10 VA 70030-3890	10 VA 70030-3891	15 VA 70030-3892	15 VA 70030-3893	20 VA 70030-3894
	5P10	2.5 VA 70030-3867	2.5 VA 70030-3868	5 VA 70030-3869	5 VA 70030-3870	5 VA 70030-3871
	10P5	10 VA 70030-3902	10 VA 70030-3903	15 VA 70030-3904	15 VA 70030-3905	20 VA 70030-3906
	10P10	2.5 VA 70030-3879	2.5 VA 70097-4240 3.75 VA 70030-3880	5 VA 70030-3881	5 VA 70097-8032	5 VA 70030-3882

		1000	1200	1500	1600	2000
5 A	5P5	10 VA 70030-3931	10 VA 70030-3932	15 VA 70030-3933	15 VA 70030-3934	20 VA 70030-3935
	5P10	2.5 VA 70097-3835	2.5 VA 70097-3971	5 VA 70030-3912	5 VA 70097-3904	5 VA 70097-4077
	10P5	10 VA 70030-3943	10 VA 70030-3944	15 VA 70030-3945	15 VA 70030-3946	20 VA 70030-3947
	10P10	2.5 VA 70030-3920	3.75 VA 70030-3921	5 VA 70030-3922	5 VA 70030-3923	5 VA 70097-4076

Special designs on request:

- any primary and secondary rated currents
- operating voltage series 1 (1,2kV)
- Cast resin grouting