



- Article features
- This protective current transformer is used for system protection in conjunction with the appropriate switching devices
 - Available in numerous protection classes
 - Sealable secondary terminal covers made of clear polycarbonate
 - Double secondary terminals on all versions for short-circuiting the secondary windings before opening the secondary circuit

Technical data	
Primary rail	30 x 15 mm, 80 x 12 mm, 100 x 10 mm
Dimensions (W x H x D)	95 x 190 x 95 mm
Instrument security factor	FS 5

Types (64)

Output	Cl.	Rated current A						
		750	800	1000	1200	1500	1600	2000
1 A	5P5	7.5 VA 70030-4400	7.5 VA 70030-4401	10 VA 70030-4402	10 VA 70030-4403	15 VA 70030-4404	15 VA 70030-4405	20 VA 70030-4406
	5P10	1.25 VA 70030-4386	1.25 VA 70030-4387	2.5 VA 70097-3934	3.75 VA 70030-4388	5 VA 70030-4389	5 VA 70030-4390	5 VA 70030-4391
	10P5	7.5 VA 70030-4408	7.5 VA 70030-4409	10 VA 70030-4410	10 VA 70030-4411	15 VA 70030-4412	15 VA 70030-4413	20 VA 70030-4414
	10P10	1.25 VA 70030-4393	2.5 VA 70030-4394	2.5 VA 70030-4395	3.75 VA 70030-4396	5 VA 70030-4397	5 VA 70030-4398	5 VA 70097-4056
5 A	5P5	7.5 VA 70030-4430	7.5 VA 70030-4431	10 VA 70030-4432	10 VA 70097-3988	15 VA 70030-4433	15 VA 70030-4434	20 VA 70030-4435
	5P10	1.25 VA 70030-4416	1.25 VA 70030-4417	2.5 VA 70097-3970	3.75 VA 70030-4418	5 VA 70030-4419	5 VA 70030-4420	5 VA 70030-4421
	10P5	7.5 VA 70030-4437	7.5 VA 70030-4438	10 VA 70030-4439	10 VA 70030-4440	15 VA 70030-4441	15 VA 70030-4442	20 VA 70030-4443
	10P10	1.25 VA 70030-4423	2.5 VA 70097-4122	2.5 VA 70030-4424	3.75 VA 70030-4425	5 VA 70030-4426	5 VA 70030-4427	5 VA 70030-4428
2500								
1 A	5P5	20 VA 70030-4407						
	5P10	7.5 VA 70030-4392						
	10P5	20 VA 70030-4415						
	10P10	7.5 VA 70030-4399						
5 A	5P5	20 VA 70030-4436						

		2500
	5P10	7.5 VA 70030-4422
	10P5	20 VA 70030-4444
	10P10	7.5 VA 70030-4429

Special designs on request:

- any primary and secondary rated currents
- operating voltage series 1 (1,2kV)
- Cast resin grouting