



- Article features
- Very compact
 - Excellent for retrofitting, as the primary circuit does not have to be interrupted
 - Especially suitable for digital measuring instruments
 - Super fast and easy installation
 - Transformer secured by UV-resistant cable ties
 - This cable conversion current transformer is supplied with multi-colour coded connection leads

Technical data	
Round conductor	Ø 28 mm
Dimensions (W × H × D)	49 × 67 × 45 mm
Instrument security factor	FS 5

Variants (12)

Article no.	Description
70006-1012	TQ 27 200/1A 0.2VA Kl. 1
70006-1013	TQ 27 250/1A 0.2VA Kl. 1
70006-1014	TQ 27 300/1A 0.2VA Kl. 1
70006-1015	TQ 27 400/1A 0.2VA Kl. 1
70006-1016	TQ 27 500/1A 0.2VA Kl. 0.5
70006-1044	TQ 27 300/5A 1VA Kl. 1
70006-1050	TQ 27 250/5A 1VA Kl. 1
70006-1051	TQ 27 400/5A 1VA Kl. 1
70006-1072	TQ 27 150A/333mV Kl. 1
70006-1073	TQ 27 200A/333mV Kl. 1
70006-1074	TQ 27 250A/333mV Kl. 1
70006-1075	TQ 27 400A/333mV Kl. 1